



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLFi.net

SL-CPL

Synthetic Centrifugal Pump Lubricant

SL-CPL utilizes the latest high-performance, full-synthetic base stocks and additives. This formulation offers an exceptional level of protection against wear, rust and corrosion, as well as outstanding resistance against oxidation and thermal breakdown.

SL-CPL is designed to provide 8,000+ hours of service.

ATTRIBUTES

- 8,000-hour oil life at 100°C discharge temperature
- Excellent thermal stability
- Resists water contamination
- Saves energy
- High flash point
- Protects against wear, rust and corrosion
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

SL-CPL Viscosities	32	46	68	100
Viscosity cP @ 0°C	311	617	917	1692
Viscosity cSt @ 40°C	30.4	45	64	105
Viscosity cSt @ 60°C	14.6	19.9	27.47	42.82
Viscosity cSt @ 80°C	8.3	10.6	14.32	21.37
Viscosity cSt @ 100°C	5.3	6.5	8.57	12.33
Flash Point °F (°C)	430 (221)	445 (229)	451 (233)	503 (262)
Demulsibility, 130°F, 30 Min	40/40/0	40/40/0	40/40/0	40/40/0
Copper Corrosion, 24 Hr	1a	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0