



7401 University Drive, Shreveport, LA 71105 - P: 318-779-0682 - F: 318-779-1762 - www.SLFi.net

SL-SS

Premium Semi-Synthetic Compressor Lubricant

SL-SS synthetic blend compressor lubricant is designed for rotary screw air compressors. This premium lubricant gives outstanding service — even in moderately severe operating conditions. With enhanced oxidative and thermal stability, SL-SS is designed to provide 4,000–6000 hours of service.

ATTRIBUTES

- 4,000–6,000 hours of oil life at 100°C discharge temperature
- Enhanced thermal and oxidative stability
- Protects against wear, rust and corrosion
- Resists water contamination
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

SL-SS Viscosities	32	46	68	100
Viscosity cP @ 0°C	330	576	1016	1672
Viscosity cSt @ 40°C	31	45	69	104
Viscosity cSt @ 60°C	14.7	20.1	29.3	42.5
Viscosity cSt @ 80°C	8.3	10.9	15.2	21.2
Viscosity cSt @ 100°C	5.3	6.7	9.0	12.2
Flash Point °F (°C)	428 (220)	442 (228)	453 (234)	501 (261)
Demulsibility	40/40/0	40/40/0	40/40/0	40/40/0
Copper Corrosion	1a	1a	1a	1a
Rust Test: Distilled Water	Pass	Pass	Pass	Pass
Rust Test: Salt Water	Pass	Pass	Pass	Pass
Foam Sequence I, II, III	0/0/0	0/0/0	0/0/0	0/0/0